

EXA ZEN 5000-2G-2S+2CQSFP Recommended For Up to 100 Gbps Throughput

World's most affordable 100 Gigabit appliance for server and networking application

High Performance appliance

Ready to use solution based on open-source technology
 PROXMOX, pfSense, OPNSense, BSD-RP, RouterOS, VyOS, DANOS
 and many other open source software / tools are tested working perfectly



2x 1 Gigabit RJ-45

2x 10 Gigabit SFP+

2x 100 Gigabit CQSFP28



Open Appliance

suitable for any implementation scenario from routing, firewall, load balancer, or just simply install popular OS such as Linux, Windows, BSD operating system can be use as medium-sized server. Simply Open.



Virtualization Support

AMD Secure Virtual Machine technology compatible with KVM, VMware, XEN, Hyper-V and any other virtual machine technology. Also works with OpenStack and containerization such as Docker.



Competitive Price

Many customer have achieved significant cost savings since implementing our solution. We offer the best value per performance that optimize and simplify your business.

AMD
RYZEN 9



MikroTik



VyOS = Router



untangle = Firewall
 Unified Treat Management



= Server

Web, DNS, Mail, NAS, Application



YOUR LOGO HERE

YOUR OS / APP

= Embedded
 System and application

OS installation request accepted : RouterOS (CHR), CentOS Linux 7, Debian Linux 9/10, Proxmox VE, Ubuntu 16/18 pfSense, OPNSense, FreeNAS, FreeBSD, Microsoft Windows Server

BITBOX already trusted by several business such as Network Access Provider, Internet Service Provider, System Integrator, Cloud Provider, Government Agencies, Educational Institutions, Schools, Hotels and many others

SPECIFICATION



Model no	EXA ZEN 5000-2G-2S+2CQ	
Form Factor	1U Rackmount	
Platform	Processor	: AMD RYZEN 9 5950x 3.4 Ghz
	CPU Socket	: AM4 PGA 1331
	Chipset	: MD X570
	Security Acceleration	: -
BIOS	32MB AMI UEFI Legal BIOS	
System Memory	Technology	: Dual Channel DDR4 3200MHz 1.2v
	Capacity	: 2x 32GB (up to 128GB ECC/UDIMM)
	Socket	: 4x 288-pin DDR4 DIMM slots
Networking	Ethernet Ports	: 2x 1GbE 2x 10GbE intel X710 2x 100 Gbe 516A CDAT 1 RJ45 Dedicated IPMI LAN Port
I/O Interface	Reset Button	: -
	LED	: Power/Storage
	Power Button	: -
	USB	: 2xUSB 3.2
	Display	: 1xVGA
	Power Input	: AC Power inlet on PSU
Storage	HDD/SSD Support	: 1x 256 GB 2.5 inch BITWIN
Misscellaneous	Watchdog	: Yes
	Internal RTC with Li Battery	: Yes
	Mounting Kit	: Yes
Cooling	Processor	: CPU Fan
	System	: 4xCooling Fan
Environmental Parameters	Temperature	: 10°C to 35°C (50°F to 95°F)
	Humidity	: 8 ~ 90% non condensing / 8 ~ 95%, non condensing
System Dimensions	(WxHxD)	: 43cm x 5,3cm x 52cm
	Weight	: 12kg
Package Dimensions	(WxHxD)	: 53cm x 12cm x 62cm
	Weight	: 13kg
Power	Type/Watts	: 300W redundant DUAL ATX PSU
	Energy efficiency	: 80 PLUS GOLD
	Input	: 90~264V@47~63Hz
Approvals and Compliance	CE, FCC Class B	

*Design and specifications product are subject to change without notice



BITBOX is high performance server platform with open networking appliance capability that support server virtualization and software defined function. Industrial grade hardware that allows your running application 24/7 seamlessly.

Designed in Sukabumi, Made In Shenzhen.

Contact us
 (+62) 859 26900 755
 info@bitbox.id
 https://bitbox.id